

MIC (48V, -15dB) VARI-PHASE 90°
 DYN. INST. LINE 0°/180°
 INSTRUMENT 75Hz OFF GAIN



3:1 6:1
 2:1 8:1
 1.5:1 100:1
 0.5ms 5ms 250ms 2s
 ATTACK RELEASE
 READ GR COMP ON
 MODEL THRESHOLD

64 500 3K
 40 400 300 1.5K 1K 6.5K
 12K 8K
 EQ IN
 SIG O/L
 -10
 OFF OUTPUT +8

PIO

MIC (48V, -15dB) VARI-PHASE 90°
 DYN. INST. LINE 0°/180°
 INSTRUMENT 75Hz OFF GAIN




3:1 6:1
 2:1 8:1
 1.5:1 100:1
 0.5ms 5ms 250ms 2s
 ATTACK RELEASE
 READ GR COMP ON
 MODEL THRESHOLD

64 500 3K
 40 400 300 1.5K 1K 6.5K
 12K 8K
 EQ IN
 SIG O/L
 -10
 OFF OUTPUT +8

PIO

MIC (48V, -15dB) VARI-PHASE 90°
 DYN. INST. LINE 0°/180°
 INSTRUMENT 75Hz OFF GAIN



3:1 6:1
 2:1 8:1
 1.5:1 100:1
 0.5ms 5ms 250ms 2s
 ATTACK RELEASE
 READ GR COMP ON
 MODEL THRESHOLD

64 500 3K
 40 400 300 1.5K 1K 6.5K
 12K 8K
 EQ IN
 SIG O/L
 -10
 OFF OUTPUT +8

PIO

MIC (48V, -15dB) VARI-PHASE 90°
 DYN. INST. LINE 0°/180°
 INSTRUMENT 75Hz OFF GAIN



3:1 6:1
 2:1 8:1
 1.5:1 100:1
 0.5ms 5ms 250ms 2s
 ATTACK RELEASE
 READ GR COMP ON
 MODEL THRESHOLD

64 500 3K
 40 400 300 1.5K 1K 6.5K
 12K 8K
 EQ IN
 SIG O/L
 -10
 OFF OUTPUT +8

PIO